

# Lino. Speedway PB2 I/O Settings

## Xitron Navigator Technical Note

December 1, 1998

Following are the jumper settings for the Xitron Speedway PB2 card I/O Address.

<b>I/O Address</b>	<b>SW1</b>	<b>SW2</b>	<b>SW3</b>	<b>SW4</b>	<b>SW5</b>	<b>SW6</b>
<b>0x280</b>	ON	ON	ON	ON	OFF	ON
<b>0x290</b>	ON	OFF	ON	ON	OFF	ON
<b>0x2A0</b>	ON	ON	OFF	ON	OFF	ON
<b>0x2B0</b>	ON	OFF	OFF	ON	OFF	ON
<b>0x2C0</b>	ON	ON	ON	OFF	OFF	ON
<b>0x2D0</b>	ON	OFF	ON	OFF	OFF	ON
<b>0x2E0</b>	ON	ON	OFF	OFF	OFF	ON
<b>0x2F0</b>	ON	OFF	OFF	OFF	OFF	ON
<b>0x300</b>	ON	ON	ON	ON	ON	OFF
<b>0x310</b>	ON	OFF	ON	ON	ON	OFF
<b>0x320</b>	ON	ON	OFF	ON	ON	OFF
<b>0x330</b>	ON	OFF	OFF	ON	ON	OFF
<b>0x340</b>	ON	ON	ON	OFF	ON	OFF